




1/24497
Locking Handle

ROTATION



ORDERING CODE

90° RH rotation
1/24497 Plant-on 'L', locking, chrome
1/24799 Plant-on 'L', non-locking, chrome
90° LH rotation
1/24854 Plant-on 'L', locking, chrome
1/24809 Plant-on 'L', non-locking, chrome

SPECIFICATION

A Handle length	105 mm
B Mounting width	23 mm
C Surface height	53 mm
D Hole centres (fixing)	35 mm
Holes tapped 10-32 UNF x 8 mm deep	

**'PLANT-ON'
'L' & 'T' HANDLES
(COLDER-STYLE
MODELS)**

An older, special design but still popular because of the unusual shape of the handle castings, particularly the deep side-walls and the narrowness of the escutcheon. All fittings are contained above panel surface, making handles fully 'plant-on'. Non-locking models also available.




**Single-sided 'FS'
keys are standard**



1/24517
Locking 'T' Handle

ROTATION



ORDERING CODE

90° RH rotation
1/24517 Plant-on 'T', locking, chrome
1/24819 Plant-on 'T', non-locking, chrome
90° LH rotation
1/24507 Plant-on 'T', locking, chrome
1/24829 Plant-on 'T', non-locking, chrome

SPECIFICATION

A Handle length	100 mm
B Mounting width	23 mm
C Surface height	53 mm
D Hole centres (fixing)	35 mm
Holes tapped 10-32 UNF x 8 mm deep	



Rotation is limited to 90° (clockwise) and 90° RH (anticlockwise) as shown, locking in both positions.



Concealed fixing only, by two screws into tapped bosses at 35 mm hole centres (1.375 inch). Gasket provided.



'FS' keys as standard with 'shuttered' keyway, optionally 'FT' or 'DLP' key types.



Chromium plated or black powder coated



- Shaft lengths
- Threaded shafts (M10)
- Special key numbers/sets

